



**Revitalize Communication with 4,000-lm-class
XGA Portable Laser Projectors**

PT-LMX420

4,000-lm-class SOLID SHINE Laser Projectors Revitalize
Communication with WUXGA Images

Key Features

Effortless Projection Anywhere, Anytime

Efficient, Reliable, and Cost-Effective

SOLID SHINE for Clear Images in Bright Light

PT-LMX420

<https://eu.connect.panasonic.com/dk/en/products/projectors/pt-lmx420>

Operating Environment	Operating temperature: 0–45 °C (32–113 °F)*12, Operating humidity: 20–80 % (no condensation)
Projector type	LCD projectors
LCD Panel Panel Size	16.0 mm (0.63 in) diagonal (4:3 aspect ratio)
LCD Panel Pixels	786,432 (1024 x 768) pixels
Light Source	Laser diodes
Light Output*1 *2	4,200 lm
Time until light output declines to 50 %*3	20,000 hours (NORMAL/QUIET)/24,000 hours (ECO)
Resolution	XGA (1024 x 768 pixels)
Contrast Ratio*1	3,000,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [1].)
Screen Size (Diagonal)	0.76–7.62 m (30–300 in), 4:3 aspect ratio
Center-to-corner zone ratio*1	85 %
Lens	1.2x manual zoom (throw ratio: 1.47–1.77:1), manual focus lens, F 1.61–1.76, f 19.1–23.0 mm
Digital Zoom Extender *4	Throw ratio: 1.47–2.22:1*5 (Corresponding value. When used together with optical zoom.)
Keystone Correction Range	Vertical: ±35 ° (Auto, Manual), Horizontal: ±35 ° (Manual)
Terminals HDMI 1/2 IN	HDMI 19-pin x 2 (Compatible with HDCP 1.4, Deep Color, 4K/30p*6 signal input), CEC supported*7
Terminals Computer 1 In	D-sub 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals Computer 2 In	D-sub 15-pin (female) x 1 (RGB/YBPBR/YCBCR)
Terminals AUDIO 1/2 IN	M3 stereo mini-jack x 2
Terminals Serial In	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)
Terminals LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX
Terminals USB(VIEWER/WIRELESS/DC OUT)	USB connector (Type A) x 1 for Memory Viewer function, optional AJ-WM50 Series Wireless Module, power supply (DC 5 V, maximum 2 A*8)
Power Supply	AC 100 V–240 V, 50/60 Hz
Power Consumption*9 Maximum power consumption	230 W
Power Consumption*9 On-mode power consumption (Light Power)	[NORMAL]: 205 W (100–240 V), 195 W (200–240 V)[ECO]: 155 W (100–240 V), 145 W (200–240 V)[QUIET]: 150 W (100–240 V), 145 W (200–240 V)
Built in Speaker	10 W monaural
Filter*10	Included (Estimated maintenance time: approx. 20,000 hours)
Operation noise*1	33 dB (NORMAL/ECO), 23 dB (QUIET)
Dimensions (W x H x D)	349 mm x 105 mm x 309 mm (13 3/4" x 4 1/8" x 12 5/32") (with feet at shortest position)
Weight with supplied lens*11	Approx. 4.2 kg (9.26 lbs)
Applicable Software	Multi Monitoring & Control Software, Projector Network Setup Software, Logo Transfer Software, Presenter Light Software for Windows®*13, Wireless Projector App for iOS/Android™*14
Note	*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 When [PICTURE MODE] is set to [DYNAMIC], [LIGHT POWER] is set to [NORMAL], [DAYLIGHT VIEW] is set to [OFF], and [AUTO POWER SAVE] is set to [OFF]. *3 Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [2], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m3 of particulate matter). Estimated time until light output declines to 50 % varies depending on environment. *4 Resolution decreases when using this function. V/H Keystone Correction and curved-screen correction are not available when using this function, and range of corner adjustment is limited. *5 When Digital Zoom Extender is set to 80 %. *6 4K signals are converted to the projector's resolution upon projection. *7 Depending on the connected CEC command-compatible device, the link control may not operate normally. *8 On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready. *9 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). *10 Filter cleaning cycle varies depending on environment. Filter can be washed and reused up to two times. Filter cleaning cycle: 20,000 hours (under dust conditions of 0.08 mg/m3), 10,000 hours (under dust conditions of 0.15 mg/m3). *11 Average value. May differ depending on the actual unit. *12 Light output is limited at operating temperatures higher than 30 °C (86 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level. When optional AJ-WM50 Series Wireless Module is attached, operating temperature range becomes 0–40 °C (32–104 °F). *13 When using Presenter Light Software, images are projected with 1280 x 800 dots or 1024 x 768 dots onto the screen. Also, your PC display resolution may be forcibly changed, and audio playback disrupted or become noisy, while images and sound are being transmitted. *14 When using the Wireless Projector app, display resolution differs depending on your iOS/Android™ device and the display device. The maximum supported display resolution is WXGA (1280 x 800).
Terminals Audio Out	M3 stereo mini-jack x 1
Protocol versions	IPv4
Control function via LAN	PJLink™ [Class 2], Crestron Connected™, AMX Device Discovery