



Evolved 1-Chip DLP™ Projectors Transform Your Experience with a Smooth, Frictionless Workflow

PT-REZ10

Key Features

High-Contrast Visuals Deepen Engagement

Flexibility and Expandability for Timesaving Workflow

New Compact Body Supports Maintenance-free Projection





PT-REZ10

<https://eu.connect.panasonic.com/se/en/products/projectors/pt-rez10>

| | |
|---|---|
| Projector type | 1-Chip DLP™ projectors |
| DLP™ Chip Panel Size | 0.8 in diagonal (16:10 aspect ratio) |
| DLP™ chip Number of Pixels | 2,304,000 (1920 x 1200 pixels) |
| Light Source | Laser diode |
| Light Output*1 *2 | 10,000 lm / 10,300 lm (Center)*3 |
| Time until light output declines to 50 %*4 | 20,000 hours (NORMAL/QUIET), 24,000 hours (ECO) |
| Resolution | WUXGA (1920 x 1200 pixels) |
| Contrast Ratio*1 | 25,000:1 (Full On/Full Off, Dynamic Contrast [3]) |
| Screen Size (Diagonal) | 70–700 inches (with supplied lens) |
| Center-to-corner zone ratio*1 | 90 % |
| Lens | PT-REZ12/REZ10/REZ80: Powered zoom (throw ratio 1.36–2.10:1 for supplied lens), powered focus; PT-REZ12L/REZ10L/REZ80L: Optional powered zoom/focus lenses |
| Lens shift Vertical(From the origin point of the lens mounter) | ±60 % (with ET-C1W400/W500/S600/T700), ±50 % (with ET-C1W300/U100) |
| Lens shift Horizontal(From the origin point of the lens mounter) | ±29 % (with ET-C1W400/W500/S600/T700), ±23 % (with ET-C1W300/U100) |
| Keystone Correction Range | Vertical: ±40 ° (±5 ° with ET-C1U100; ±10 ° with ET-C1W300; ±16 ° with ET-C1W400; ±22 ° with ET-C1W500), Horizontal: ±40 ° (±3 ° with ET-C1U100; ±5 ° with ET-C1W300; ±10 ° with ET-C1W400; ±15 ° with ET-C1W500) |
| Terminals HDMI™ 1/2 IN | HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input*5) |
| Terminals DisplayPort™ | DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input*5) |
| Terminals Multi Sync In | BNC x 1 |
| Terminals Multi Sync Out | BNC x 1 |
| Terminals Serial In | D-sub 9-pin (female) x 1 for external control (RS-232C compliant) |
| Terminals Serial Out | D-sub 9-pin (male) x 1 for link control (RS-232C compliant) |
| Terminals REMOTE 1 IN | M3 stereo mini-jack x 1 for wired remote control |
| Terminals REMOTE 1 OUT | M3 stereo mini-jack x 1 for link control (for wired remote control) |
| Terminals Remote 2 In | D-sub 9-pin (female) x 1 for external control (parallel) |
| Terminals LAN | RJ-45 x 1 for network connection, PjLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible |
| Terminals USB | USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory |
| Terminals DC Out | USB Type A x 1 (for power supply, DC 5 V, 2 A) |
| Terminals Expansion Slot | Open slot for function boards, Intel® SDM compatible |
| Protocol versions | IPv4, IPv6*6 |
| Power Supply | AC 100–240 V, 50/60 Hz |
| Power Consumption*7 Maximum power consumption | 840 W (8.8–3.7 A) (850 VA) (Power consumption is 810 W at AC 200–240 V) |
| Power Consumption*7 On-mode power consumption (Operating mode) Nomal | 700 W (AC 100–120 V), 675 W (AC 200–240 V) |
| Power Consumption*7 On-mode power consumption (Operating mode) ECO | 540 W (AC 100–120 V), 525 W (AC 200–240 V) |
| Power Consumption*7 On-mode power consumption (Operating mode) QUIET | 530 W (AC 100–120 V), 515 W (AC 200–240 V) |
| Operation noise*1 | 36 dB (NORMAL/ECO), 33 dB (QUIET) |
| Dimensions (W x H x D) | PT-REZ12/REZ10/REZ80: 498 x 212 x 648 mm (19 19/32" x 8 11/32" x 25 1/2") (With feet at shortest position) PT-REZ12L/REZ10L/REZ80L: 498 x 212 x 538 mm (19 19/32" x 8 11/32" x 21 3/16") (With feet at shortest position) |
| Weight*7 | PT-REZ12/REZ10/REZ80: Approx. 28.7 kg (63.27 lbs) (with supplied lens), PT-REZ12L/REZ10L/REZ80L: Approx. 27.0 kg (59.52 lbs) (without lens) |
| Operating Environment | Operating temperature: 0–45 °C (32–113 °F)*9, operating humidity: 10–80 % (no condensation) |
| Applicable Software | Logo Transfer Software, Multi Monitoring & Control Software, Projector Network Setup Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™ |
| Control function via LAN | Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net DMX, AMX® DD, and PjLink™ (Class 2) |

Note

*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118:2020 international standards. Value is the average of all products when shipped.
*2 When [OPERATING MODE] is set to [NORMAL]. *3 Average light-output value of all shipped products measured at the center of the screen in NORMAL Mode. *4 Around this time, light output will have decreased by approximately 50%. IEC62087:2008 Broadcast Contents, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. The estimated time until light output declines to 50% varies depending on the environment. *5 4K signals are converted to WUXGA (1920 x 1200 pixels). *6 Optional AJ-WM50 Series Wireless Module is not compatible with IPv6. *7 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118:2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). *8 Average value. May differ depending on the actual unit. *9 When the optional AJ-WM50 Series wireless module is attached, the operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).