

### PRODUCT LEAFLET

## Indoor monitor housing



#### 092.1500.1 Flat panel indoor housing for 46-49 inch monitor

To protect your monitor SmartMetals supplies a complete line of monitor housings for in- as well as outdoor use. The housings are standard equipped with a hinging front and hardened safety glass in an extra clear quality. The housings for outdoor use are fitted with active ventilation, thermostatically controlled heating elements and a dust filter. A wall mount and VESA mount for the monitor are standard supplied. The standard colour of the housing is white with a black frame around the monitor; white for the monitor to protect from external heat, black for the frame for contrast. Other colours are available on request. The enclosures are available for portrait as well as landscape position and the outdoor models are produced according to the IPx4 norm.

The 092.1500 & 092.1600 series are suitable for monitors till 700cd and a max. depth of 85 mm, the 092.1700 are suited for the high brightness monitors up to 2500cd and a max. depth of 140 mm. Due to the several variations in high brightness, these 092.1700 housings are exclusively custom-built. Describe your brand and model of monitor in the description of your quote enquiry.



## PRODUCT LEAFLET

# Indoor monitor housing

#### **Features**

**Weight:** 60.00 kg **Colour:** White

Screen position: Landscape, Portrait


Inch range: 46 - 49 inch Mobile / fixed: Fixed **Bracket/interface:** Included **Type bracket/interface:** VESA

Range bracket/interface: Max. VESA 600-400 / 400-600 Other information: Other colours available on request Suitable for max. monitor dimensions 1118 x 713 x 85 mm

- VESA 400x400 > Max VESA center offset 113 mm

- VESA 600x600 > Max VESA center offset 13 mm

- Cooling: Passive (Air exhaust holes surface: 27208 mm²)



47" Display: A= 1040 mm, B= 585 mm

49" Display: A= 1078 mm, B= 608 mm

48" Display: A= 1054 mm, B= 592.5 mm